

# Package ‘NPBayesImputeCat’

December 1, 2025

**Type** Package

**Title** Non-Parametric Bayesian Multiple Imputation for Categorical Data

**Version** 0.6

**Date** 2025-11-26

**Maintainer** Jingchen Hu <jingchen.monika.hu@gmail.com>

**Description** These routines create multiple imputations of missing at random categorical data, and create multiply imputed synthesis of categorical data, with or without structural zeros. Imputations and syntheses are based on Dirichlet process mixtures of multinomial distributions, which is a non-parametric Bayesian modeling approach that allows for flexible joint modeling, described in Manrique-Vallier and Reiter (2014) <[doi:10.1080/10618600.2013.844700](https://doi.org/10.1080/10618600.2013.844700)>.

**License** GPL (>= 3)

**Depends** Rcpp (>= 0.10.2)

**Imports** methods, rlang, reshape2, ggplot2, dplyr, bayesplot, coda

**LinkingTo** Rcpp

**RcppModules** clcm

**NeedsCompilation** yes

**Repository** CRAN

**Author** Quanli Wang [aut],  
Daniel Manrique-Vallier [aut],  
Jerome P. Reiter [aut],  
Jingchen Hu [aut, cre]

**Date/Publication** 2025-12-01 15:40:16 UTC

## Contents

NPBayesImputeCat-package . . . . .	2
compute_probs . . . . .	4
CreateModel . . . . .	4
DPMPM_nozeros_imp . . . . .	6
DPMPM_nozeros_syn . . . . .	7
DPMPM_zeros_imp . . . . .	8

fit_GLMs . . . . .	9
GetDataFrame . . . . .	9
GetMCZ . . . . .	10
kstar_MCMCdiag . . . . .	11
Lcm . . . . .	12
marginal_compare_all_imp . . . . .	14
marginal_compare_all_syn . . . . .	14
MCZ . . . . .	15
pool_estimated_probs . . . . .	15
pool_fitted_GLMs . . . . .	16
Rcpp_Lcm-class . . . . .	16
ss16pusa_ds_MCZ . . . . .	16
ss16pusa_mi_MCZ . . . . .	17
ss16pusa_sample_nozeros . . . . .	17
ss16pusa_sample_nozeros_miss . . . . .	18
ss16pusa_sample_zeros . . . . .	18
ss16pusa_sample_zeros_miss . . . . .	19
UpdateX . . . . .	19
X . . . . .	20

<b>Index</b>	<b>21</b>
--------------	-----------

---

NPBayesImputeCat-package

*Bayesian Multiple Imputation for Large-Scale Categorical Data with  
Structural Zeros*

---

## Description

This package implements a fully Bayesian, joint modeling approach to multiple imputation for categorical data based on latent class models with structural zeros. The idea is to model the implied contingency table of the categorical variables as a mixture of independent multinomial distributions, estimating the mixture distributions nonparametrically with Dirichlet process prior distributions. Mixtures of multinomials can describe arbitrarily complex dependencies and are computationally expedient, so that they are effective general purpose multiple imputation engines. In contrast to other approaches based on loglinear models or chained equations, the mixture models avoid the need to specify (potentially many) models, which can be a very time-consuming task with no guarantee of a theoretically coherent set of models. The package is designed to include for structural zeros, i.e., certain combinations of variables are not possible a priori.

## Details

Package: NPBayesImputeCat  
 Type: Package  
 Version: 0.4  
 Date: 2021-06-30  
 License: GPL(>=3)

**Author(s)**

Quanli Wang, Daniel Manrique-Vallier, Jerome P. Reiter and Jingchen Hu

Maintainer: Quanli Wang<quanli@stat.duke.edu>

**References**

Manrique-Vallier, D. and Reiter, J.P. (2013), "Bayesian Estimation of Discrete Multivariate Latent Structure Models with Structural Zeros", JCGS.

Si, Y. and Reiter, J.P. (2013), "Nonparametric Bayesian multiple imputation for incomplete categorical variables in large-scale assessment surveys", Journal of Educational and Behavioral Statistics, 38, 499 - 521

Manrique-Vallier, D. and Reiter, J.P. (2014), "Bayesian Multiple Imputation for Large-Scale Categorical Data with Structural Zeros", Survey Methodology.

**Examples**

```
require(NPBayesImputeCat)
#Please use NYexample data set for a more realistic example
data('NYMockexample')

#create the model
model <- CreateModel(X,MCZ,10,10000,0.25,0.25,8888)

#run 1 burnins, 2 mcmc iterations and thin every 2 iterations
model$Run(1,2,2,TRUE)

#retrieve parameters from the final iteration
result <- model$snapshot

#convert ImputedX matrix to dataframe, using proper factors/names etc.
ImputedX <- GetDataFrame(result$ImputedX,X)
#View(ImputedX)

#Most exhauststic examples can be found in the demo below
#demo(example_short)
#demo(example)
```

---

compute_probs	<i>Estimating marginal and joint probabilities in imputed or synthetic datasets</i>
---------------	---

---

### Description

Estimating marginal and joint probabilities in imputed or synthetic datasets

### Usage

```
compute_probs(InputData, varlist)
```

### Arguments

InputData	a list of imputed or synthetic datasets
varlist	a list of variable names (or combination of names) to evaluate (marginal or joint) probabilities for

### Value

Results: a list of marginal and joint probability results after combining rules

---

CreateModel	<i>Create and initialize the Lcm model object</i>
-------------	---

---

### Description

CreateModel creates and initializes an Lcm [Lcm](#) object for non-parametric multiple imputation of discrete multivariate categorical data with or without structural zeros.

### Usage

```
CreateModel(X, MCZ, K, Nmax, aalpha, balpha, seed)
```

### Arguments

X	a data frame with the dataset with missing values. All variables must be un-ordered factors.
MCZ	a dataframe with the definition of the structural zeros. Placeholder components are represented with NAs. Variables in MCZ must be factors with the same levels as X. Rows do not need to define disjoint regions of the contingency table. See Manrique-Vallier and Reiter (2014) for details of the definition of structural zeros. MCZ should be set to NULL when there are no structure zeros.
K	the maximum number of mixture components.

Nmax	An upper truncation limit for the augmented sample size. This parameter will be ignored(set to 0) when there is no structural zeros.
aalpha	the hyper parameter 'a' for alpha in stick-breaking prior distribution.
balpha	the hyper parameter 'b' for alpha in stick-breaking prior distribution.
seed	the random seed for sampling. When setting to NULL(default), the random seed will be set randomly.

## Details

This function should be the first function one should call to use the 'NPBayesImputeCat' library. The returned model is a Lcm object. See ?Lcm for more details on the fields available and their arguments.

## Value

CreateModel returns an Lcm object. The returned model object will be referenced in all subsequent calls.

## References

Manrique-Vallier, D. and Reiter, J.P. (2013), "Bayesian Estimation of Discrete Multivariate Latent Structure Models with Structural Zeros", JCGS.

Si, Y. and Reiter, J.P. (2013), "Nonparametric Bayesian multiple imputation for incomplete categorical variables in large-scale assessment surveys", Journal of Educational and Behavioral Statistics, 38, 499 - 521

Manrique-Vallier, D. and Reiter, J.P. (2014), "Bayesian Multiple Imputation for Large-Scale Categorical Data with Structural Zeros", Survey Methodology.

## Examples

```
require(NPBayesImputeCat)
#Please use NYexample data set for a more realistic example
data('NYMockexample')

#create the model
model <- CreateModel(X,MCZ,10,10000,0.25,0.25,8888)

#run 1 burnins, 2 mcmc iterations and thin every 2 iterations
model$Run(1,2,2,FALSE)

#retrieve parameters from the final iteration
result <- model$snapshot

#convert ImputedX matrix to dataframe, using proper factors/names etc.
ImputedX <- GetDataFrame(result$ImputedX,X)
#View(ImputedX)
```

---

DPMPM_nozeros_imp	<i>Use DPMPM models to impute missing data where there are no structural zeros</i>
-------------------	--

---

### Description

Use DPMPM models to impute missing data where there are no structural zeros

### Usage

```
DPMPM_nozeros_imp(X, nrun, burn, thin, K, aalpha, balpha, m, seed, silent)
```

### Arguments

X	data frame for the data containing missing values
nrun	number of mcmc iterations
burn	number of burn-in iterations
thin	thinning parameter for outputting iterations
K	number of latent classes
aalpha	the hyperparameters in stick-breaking prior distribution for alpha
balpha	the hyperparameters in stick-breaking prior distribution for alpha
m	number of imputations
seed	choice of random seed
silent	Default to TRUE. Set this parameter to FALSE if more iteration info are to be printed

### Value

impdata	m imputed datasets
origdata	original data containing missing values
alpha	saved posterior draws of alpha, which can be used to check MCMC convergence
kstar	saved number of occupied mixture components, which can be used to track whether K is large enough

---

DPMPM_nozeros_syn	<i>Use DPMPM models to synthesize data where there are no structural zeros</i>
-------------------	--

---

## Description

Use DPMPM models to synthesize data where there are no structural zeros

## Usage

```
DPMPM_nozeros_syn(X, dj, nrun, burn, thin, K, aalpha, balpha, m, vars, seed, silent)
```

## Arguments

X	data frame for the original data
dj	a vector recording the number of categories of the variables
nrun	number of mcmc iterations
burn	number of burn-in iterations
thin	thinning parameter for outputting iterations
K	number of latent classes
aalpha	the hyperparameters in stick-breaking prior distribution for alpha
balpha	the hyperparameters in stick-breaking prior distribution for alpha
m	number of synthetic datasets
vars	the names of variables to be synthesized
seed	choice of random seed
silent	Default to TRUE. Set this parameter to FALSE if more iteration info are to be printed

## Value

syndata	m synthetic datasets
origdata	original data
alpha	saved posterior draws of alpha, which can be used to check MCMC convergence
kstar	saved number of occupied mixture components, which can be used to track whether K is large enough

---

DPMPM_zeros_imp	<i>Use DPMPM models to impute missing data where there are no structural zeros</i>
-----------------	--

---

### Description

Use DPMPM models to impute missing data where there are no structural zeros

### Usage

```
DPMPM_zeros_imp(X, MCZ, Nmax, nrun, burn, thin, K, aalpha, balpha, m, seed, silent)
```

### Arguments

X	data frame for the data containing missing values
MCZ	data frame containing the structural zeros definition
Nmax	an upper truncation limit for the augmented sample size
nrun	number of mcmc iterations
burn	number of burn-in iterations
thin	thinning parameter for outputting iterations
K	number of latent classes
aalpha	the hyperparameters in stick-breaking prior distribution for alpha
balpha	the hyperparameters in stick-breaking prior distribution for alpha
m	number of imputations
seed	choice of random seed
silent	Default to TRUE. Set this parameter to FALSE if more iteration info are to be printed

### Value

impdata	m imputed datasets
origdata	original data containing missing values
alpha	save posterior draws of alpha, which can be used to check MCMC convergence
kstar	saved number of occupied mixture components, which can be used to track whether K is large enough
Nmax	saved posterior draws of the augmented sample size, which can be used to check MCMC convergence



fit\_GLMs

*Fit GLM models for imputed or synthetic datasets***Description**

Fit GLM models for imputed or synthetic datasets

**Usage**

```
fit_GLMs(InputData, exp)
```

**Arguments**

InputData	a list of imputed or synthetic datasets
exp	GLM expression (for polr and nnet, those libraries should be loaded first)

**Value**

Results: a list of GLM results

GetDataFrame

*Convert imputed data to a dataframe, using the same setting from original input data.***Description**

This is a utility function to convert the imputed data matrix to a dataframe. This function will be implemented as a RCPP internal function later on.

**Usage**

```
GetDataFrame(dest, from, cols = 1:NCOL(from))
```

**Arguments**

dest	the imputed output data matrix.
from	the original input dataframe.
cols	optinal. Always use default for now.

**Value**

The returned dataframe object for imputed data.

## Examples

```
require(NPBayesImputeCat)
#Please use NYexample data set for a more realistic example
data('NYMockexample')

#create the model
model <- CreateModel(X,MCZ,10,10000,0.25,0.25,8888)

#run 1 burnins, 2 mcmc iterations and thin every 2 iterations
model$Run(1,2,2,TRUE)

#retrieve parameters from the final iteration
result <- model$snapshot

#convert ImputedX matrix to dataframe, using proper factors/names etc.
ImputedX <- GetDataFrame(result$ImputedX,X)
#View(ImputedX)
```

---

GetMCZ

---

*Convert disjointed structural zeros to a dataframe, using the same setting from original structural zero data.*


---

## Description

This is a utility function to convert the disjointed structural zero matrix to a dataframe. This function will be implemented as a RCPP internal function later on.

## Usage

```
GetMCZ(dest, from, mcz, cols = 1:NCOL(from))
```

## Arguments

dest	the output data matrix for disjointed structural zeros.
from	the original input dataframe.
mcz	the original input dataframe for structural zeros.
cols	optinal. Always use default for now.

## Value

The returned dataframe object for disjointed structural zeros.

## References

Manrique-Vallier, D. and Reiter, J.P. (2013), "Bayesian Estimation of Discrete Multivariate Latent Structure Models with Structural Zeros", JCGS.

Si, Y. and Reiter, J.P. (2013), "Nonparametric Bayesian multiple imputation for incomplete categorical variables in large-scale assessment surveys", Journal of Educational and Behavioral Statistics, 38, 499 - 521

Manrique-Vallier, D. and Reiter, J.P. (2014), "Bayesian Multiple Imputation for Large-Scale Categorical Data with Structural Zeros", Survey Methodology.

---

kstar_MCMCdiag	<i>Perform MCMC diagnostics for kstar</i>
----------------	---

---

## Description

A helper function to perform MCMC diagnostics for kstar

## Usage

```
kstar_MCMCdiag(kstar, nrun, burn, thin)
```

## Arguments

kstar	the vector output of kstar from running the DPMPM model
nrun	number of MCMC iterations used in running the DPMPM model
burn	number of burn-in iterations used in running the DPMPM model
thin	number of thinning used in running the DPMPM model

## Value

Traceplot	the traceplot of kstar post burn-in and thinning
Autocorrplot	the autocorrelation plot of kstar post burn-in and thinning

Lcm

Class "Rcpp\_Lcm"

## Description

This class implements the MCMC sampler for non-parametric imputation of discrete multivariate data described in Manrique-Vallier and Reiter (2014). It provides methods for updating and monitoring the sampler.

## Details

Rcpp\_lcm objects should be created with [CreateModel](#). Please see the examples in the demo folder for more detailed explanation on model fitting and parameter tracing.

## Extends

Class "C++Object", directly.

All reference classes extend and inherit methods from "[envRefClass](#)".

## Fields

**CurrentIteration:** the total number of iterations that have been run so far.

**EnableTracer:** to check tracer status or to enable/disable the tracer.

**MCZ:** the disjointed structural zero matrix.

**snapshot:** retrieve a list with the current state of all the parameters in the sampler, including the imputed sample. A call the the "snapshot" method returns a list with the following components:

**alpha:** the concentration parameter of the stick breaking prior.

**k\_star:** the effective number number of latent classes (mixture components)

**Nmis:** the size of the augmented sample.

**nu:** a vector with the mixture weights

**z:** a matrix with the current latent class assignment of each member of the sample

**ImputedX:** the current raw imputed dataset. Use [GetDataFrame](#) to convert the raw data to a data frame of factors as defined in the input data set.

**psi:** The conditional multinomial probabilities. A  $L_{\max} * K * J$  array, where  $L_{\max}$  is the maximum number of levels of all discrete factors in the dataset,  $J$  is the number of factors in the dataset, and  $K$  is the number of latent classes. Since variables might have different numbers of levels, unused entries in the first dimension are filled with NAs to complete  $L_{\max}$ .

**traceable:** list of model parameters that can be traced by the tracer.

**traced:** list of model parameters that are traced.

## Methods

`SetTrace(paralist,num_of_iterations)`: set parameters to be traced.

**paralist**: a list of parameters to be traced.

**num\_of\_iterations**: the maximum number of traced iterations.

`Run(burnin, iter, thinning,silent)`: run MCMC iterations.

**burnin**: number of burn in iterations.

**iter**: number of MCMC iterations.

**thinning**: thinning parameter.

**silent**: boolean indication if more iteration should be printed.

`Resume()`: resume from an interrupted call to run method.

`Parameters(paralist)`: retrieve a selected list of model parameters from last MCMC iteration.

**paralist**: a list of parameters to be traced.

`GetTrace()`: retrieve all traced iterations. Returns a list with all the parameters set using the method `SetTrace()`. See description of `snapshot(reference)` method for a description of the parameters.

## References

Manrique-Vallier, D. and Reiter, J.P. (2013), "Bayesian Estimation of Discrete Multivariate Latent Structure Models with Structural Zeros", JCGS.

Si, Y. and Reiter, J.P. (2013), "Nonparametric Bayesian multiple imputation for incomplete categorical variables in large-scale assessment surveys", Journal of Educational and Behavioral Statistics, 38, 499 - 521

Manrique-Vallier, D. and Reiter, J.P. (2014), "Bayesian Multiple Imputation for Large-Scale Categorical Data with Structural Zeros", Survey Methodology.

## Examples

```
require(NPBayesImputeCat)
#Please use NYexample data set for a more realistic example
data('NYMockexample')

#create the model
model <- CreateModel(X,MCZ,10,10000,0.25,0.25,8888)

#run 1 burnins, 2 mcmc iterations and thin every 2 iterations
model$Run(1,2,2,TRUE)

#retrieve parameters from the final iteration
result <- model$snapshot

#convert ImputedX matrix to dataframe, using proper factors/names etc.
ImputedX <- GetDataFrame(result$ImputedX,X)
#View(ImputedX)
```

---

marginal_compare_all_imp	<i>Plot estimated marginal probabilities from observed data vs imputed datasets</i>
--------------------------	---

---

**Description**

Plot estimated marginal probabilities from observed data vs imputed datasets

**Usage**

```
marginal_compare_all_imp(obsdata, impdata, vars)
```

**Arguments**

obsdata	the observed data
impdata	the list of m imputed datasets
vars	the variable of interest

**Value**

Plot	the barplot
Comparison	a table of marginal probabilities from observed data vs imputed datasets

---

marginal_compare_all_syn	<i>Plot estimated marginal probabilities from observed data vs synthetic datasets</i>
--------------------------	---

---

**Description**

Plot estimated marginal probabilities from observed data vs synthetic datasets

**Usage**

```
marginal_compare_all_syn(obsdata, syndata, vars)
```

**Arguments**

obsdata	the observed data
syndata	the list of m imputed datasets
vars	the variable of interest

**Value**

Plot	the barplot
Comparison	a table of marginal probabilities from observed data vs imputed datasets

---

MCZ	<i>Example dataframe for structural zeros based on the NYMockexample dataset.</i>
-----	---

---

**Description**

Example dataframe for structural zeros based on the NYMockexample dataset. It contains 8 structural zero cases with 10 variables.

- [,1] AGE = 15 and EDUC = 8
- [,2] AGE = 16 and VESTAT = 2
- [,3] OWNERSHIP = 0 and MORTGAGE = 4
- [,4] AGE = 17 and EDUC = 11
- [,5] AGE = [36, 50] and EMPSTAT = 0
- [,6] AGE > 70 and DISABWRK = 0
- [,7] AGE < 15 and EDUC = 10
- [,8] OWNERSHIP = 2 and MORTGAGE = 1

---

pool_estimated_probs	<i>Pool probability estimates from imputed or synthetic datasets</i>
----------------------	--

---

**Description**

Pool probability estimates from imputed or synthetic datasets

**Usage**

```
pool_estimated_probs(ComputeProbsResults, method =  
                      c("imputation", "synthesis_full", "synthesis_partial"))
```

**Arguments**

- ComputeProbsResults  
output from the compute\_probs function
- method  
choose between "imputation", "synthesis\_full", "synthesis\_partial"

**Value**

Results: a list of marginal and joint probability results after combining rules

---

pool_fitted_GLMs	<i>Pool estimates of fitted GLM models in imputed or synthetic datasets</i>
------------------	---

---

**Description**

Pool estimates of fitted GLM models in imputed or synthetic datasets

**Usage**

```
pool_fitted_GLMs(GLMResults, method =  
                  c("imputation", "synthesis_full", "synthesis_partial"))
```

**Arguments**

GLMResults	output from the fit_GLMs function
method	choose between "imputation", "synthesis_full", "synthesis_partial"

**Value**

Results: a list of GLM results after combining rules

---

Rcpp_Lcm-class	<i>Rcpp implemenation of the <a href="#">Lcm</a> functions</i>
----------------	--

---

**Description**

This is the Rcpp implementation of the model class Lcm. All exposed functions and properties are documented in [Lcm](#).

---

ss16pusa_ds_MCZ	<i>Example dataframe for structrual zeros based on the ss16pusa_sample_zeros dataset.</i>
-----------------	---

---

**Description**

Example dataframe for structrual zeros based on the ss16pusa\_sample\_zeros dataset. It contains 8 structural zero cases with 5 variables.

- [,1] AGEP = 16 and SCHL = Bachelor's degree
- [,2] AGEP = 16 and SCHL = Doctorate degree
- [,3] AGEP = 16 and SCHL = Master's degree
- [,4] AGEP = 16 and SCHL = Professional degree
- [,5] AGEP = 17 and SCHL = Bachelor's degree



- [,6] AGEP = 17 and SCHL = Doctorate degree
- [,7] AGEP = 17 and SCHL = Master's degree
- [,8] AGEP = 17 and SCHL = Professional degree

---

ss16pusa_mi_MCZ	<i>Example dataframe for structural zeros based on the ss16pusa_sample_zeros dataset.</i>
-----------------	---

---

### Description

Example dataframe for structural zeros based on the ss16pusa\_sample\_zeros dataset. It contains 8 structural zero cases with 5 variables.

- [,1] AGEP = 16 and SCHL = Bachelor's degree
- [,2] AGEP = 16 and SCHL = Doctorate degree
- [,3] AGEP = 16 and SCHL = Master's degree
- [,4] AGEP = 16 and SCHL = Professional degree
- [,5] AGEP = 17 and SCHL = Bachelor's degree
- [,6] AGEP = 17 and SCHL = Doctorate degree
- [,7] AGEP = 17 and SCHL = Master's degree
- [,8] AGEP = 17 and SCHL = Professional degree

---

ss16pusa_sample_nozeros	<i>Example dataframe for input categorical data without structural zeros (without missing values).</i>
-------------------------	--

---

### Description

Example dataframe for input categorical data without structural zeros (without missing values). It contains 1000 observations and 3 variables.

- [,1] MAR marital status 5 levels: Married; Widowed; Divorced; Separated; Never married.
- [,2] SEX sex 2 levels: Male; Female.
- [,3] WKL When last worked 3 levels: Within the last 12 months; 1-5 years ago; Over 5 years ago or never worked.

---

ss16pusa\_sample\_nozeros\_miss

*Example dataframe for input categorical data without structural zeros (with missing values).*

---

### Description

Example dataframe for input categorical data without structural zeros (with missing values). It contains 1000 observations and 3 variables.

[,1]	MAR	marital status	5 levels: Married; Widowed; Divorced; Separated; Never married.
[,2]	SEX	sex	2 levels: Male; Female.
[,3]	WKL	When last worked	3 levels: Within the last 12 months; 1-5 years ago; Over 5 years ago or never worked.

---

ss16pusa\_sample\_zeros *Example dataframe for input categorical data with structural zeros (without missing values).*

---

### Description

Example dataframe for input categorical data with structural zeros (without missing values). It contains 1000 observations and 5 variables.

[,1]	AGEP	age	7 levels: 16; 17; [18, 24]; [25, 35]; [36, 50]; [51, 70]; (70, ).
[,2]	MAR	marital status	5 levels: Married; Widowed; Divorced; Separated; Never married.
[,3]	SCHL	educational attainment	9 levels: Up to K0; Some K12, no diploma; High school diploma or GED; Some college, no degree; Associate's degree; Bachelor's degree; Master's degree; Professional degree; Doctorate degree.
[,4]	SEX	sex	2 levels: Male; Female.
[,5]	WKL	When last worked	3 levels: Within the last 12 months; 1-5 years ago; Over 5 years ago or never worked.

---

ss16pusa\_sample\_zeros\_miss

*Example dataframe for input categorical data with structural zeros (with missing values).*

---

### Description

Example dataframe for input categorical data with structural zeros (with missing values). It contains 1000 observations and 5 variables.

[,1]	AGEP	age	7 levels: 16; 17; [18, 24]; [25, 35]; [36, 50]; [51, 70]; (70, ).
[,2]	MAR	marital status	5 levels: Married; Widowed; Divorced; Separated; Never married.
[,3]	SCHL	educational attainment	9 levels: Up to K0; Some K12, no diploma; High school diploma or GED; Some college, no degree; Associate's degree; Bachelor's degree; Master's degree; Professional degree; Doctorate degree.
[,4]	SEX	sex	2 levels: Male; Female.
[,5]	WKL	When last worked	3 levels: Within the last 12 months; 1-5 years ago; Over 5 years ago or never worked.

---

UpdateX

*Allow user to update the model with data matrix of same kind.*

---

### Description

Allow user to replace initial matrix with a new data matrix of same size and same number of factors. This is not intended for general use and is only useful for very specific circumstance.

### Usage

```
UpdateX(model, X)
```

### Arguments

model	The Rcpp model object created by the CreateModel function.
X	a data frame with the dataset with missing values. All variables must be un-ordered factors.

---

X *Example dataframe for input categorical data with missing values based on the NYMockexample dataset.*

---

### Description

Example dataframe for input categorical data with missing values based on the NYMockexample dataset. It contains 2000 observations and 10 variables.

[,1]	OWNERSHIP	ownership of dwelling	3 levels: N/A; Owned or being bought (loan); Rented.
[,2]	MORTGAGE	mortgate status	4 levels: N/A; No, owned free and clear; Yes, mortgaged / deed of trust or similar debt; Yes, contract to purchase.
[,3]	AGE	age	9 levels: [0, 14]; 15; 16; 17; [18, 24]; [25, 35]; [36, 50]; 9 [51, 70]; [71, ).
[,4]	SEX	sex	2 levels: Male; Female.
[,5]	MARST	marital status	6 levels: Married, spouse present; Married, spouse absent; Separated; Divorced; Widowed; Never married / single.
[,6]	RACESING	single race identification	5 levels: White; Black; American Indian / Alaska Native; Asian and / or Pacific Islander; Other race, non-Hispanic.
[,7]	EDUC	educational attainment	11 levels: N/A or no schooling; Nursery school to grade 4; Grade 5, 6, 7, or 8; Grade 9; Grade 10; Grade 11; Grade 12; 1 year of college; 2 years of college; 4 years of college; 5+ years of college.
[,8]	EMPSTAT	employment status	4 levels: N/A; Employed; Unemployed; Not in labor force.
[,9]	DISABWRK	work disability status	3 levels: N/A; No disability that affects work; Disability causes difficulty working.
[,10]	VESTAT	veteran status	3 levels: N/A; Not a veteran; Veteran.

# Index

- \* **classes**
  - Lcm, [12](#)
- \* **package**
  - NPBayesImputeCat-package, [2](#)
- compute\_probs, [4](#)
- CreateModel, [4](#), [12](#)
- DPMPM\_nozeros\_imp, [6](#)
- DPMPM\_nozeros\_syn, [7](#)
- DPMPM\_zeros\_imp, [8](#)
- envRefClass, [12](#)
- fit\_GLMs, [9](#)
- GetDataFrame, [9](#), [12](#)
- GetMCZ, [10](#)
- kstar\_MCMCdiag, [11](#)
- Lcm, [4](#), [12](#), [16](#)
- marginal\_compare\_all\_imp, [14](#)
- marginal\_compare\_all\_syn, [14](#)
- MCZ, [15](#)
- NPBayesImputeCat
  - (NPBayesImputeCat-package), [2](#)
- NPBayesImputeCat-package, [2](#)
- pool\_estimated\_probs, [15](#)
- pool\_fitted\_GLMs, [16](#)
- Rcpp\_Lcm-class, [16](#)
- ss16pusa\_ds\_MCZ, [16](#)
- ss16pusa\_mi\_MCZ, [17](#)
- ss16pusa\_sample\_nozeros, [17](#)
- ss16pusa\_sample\_nozeros\_miss, [18](#)
- ss16pusa\_sample\_zeros, [18](#)
- ss16pusa\_sample\_zeros\_miss, [19](#)
- UpdateX, [19](#)
- X, [20](#)